

INDOOR PRODUCT

CEILING LIGHT SERIES

CEILING LIGHT SERIES

High quality engineering plastic, PC lamp body, spread of PMMA lamp shade, frosted surface, high transmission performance, pure aluminum circuit boards, high brightness SMD LED, straight down lighting. IP20 protection grade, built-in drivers. The installation type suction a top. mainly used in the stairs passage or home room and other places of indoor lighting.



WNZ0038

37



Material: Metal housing, PC cover

Power: 18W

CCT: 3000K/4000K/6000K


Color rendering index: Ra≥80

Driver: Built-in LED constant current driver

Operating temperature: -20°C~40°C



Beam Angle:



WNZ00



Material: Metal housing, PC cover

Power: 18W

CCT: 3000K/4000K/6000K

Color rendering index: Ra≥80

Driver: Built-in LED constant current driver

Operating temperature: -20°C~40°C



Beam Angle:



WNZ0040



Material: Metal housing, PC cover

Power: 18W

CCT: 3000K/4000K/6000K


Color rendering index: Ra≥80

Driver: Built-in LED constant current driver

Operating temperature: -20°C~40°C



Beam Angle:



WNZ0039



Material: Metal housing, PC cover

Power: 24W

CCT: 3000K/4000K/6000K


Color rendering index: Ra≥80

Driver: Built-in LED constant current driver

Operating temperature: -20°C~40°C



Beam Angle:



WNZ0036



Material: Metal housing, PC cover

Power: 18W

CCT: 3000K/4000K/6000K


Color rendering index: Ra≥80

Driver: Built-in LED constant current driver

Operating temperature: -20°C~40°C




Beam Angle:






WNK11043-S

Material: Metal housing, PC cover
 Power: 12W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C



WNK11043-M

Material: Metal housing, PC cover
 Power: 18W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C




WNK11043-L

Material: Metal housing, PC cover
 Power: 24W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C




WNK11048-S

Material: Metal housing, PC cover
 Power: 24W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C




WNK11048-M

Material: Metal housing, PC cover
 Power: 36W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C




WNK11044-S

Material: Metal housing, PC cover
 Power: 12W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C




WNK11044-M

Material: Metal housing, PC cover
 Power: 18W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C




WNK11044-L

Material: Metal housing, PC cover
 Power: 24W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C




WNK11051-S

Material: Metal housing, PC cover
 Power: 36W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C



WNK11051-M

Material: Metal housing, PC cover
 Power: 64W
 CCT: 3000K/4000K/6000K
 Color rendering index: Ra≥80
 Driver: Built-in LED constant current driver
 Operating temperature: -20°C~40°C






WNZ00004



Material: PC
 Power: 18W
 CCT: 4000K/5000K/6000K
 Light source: EPISTAR SMD
 Light output: 1800lm
 Color rendering index: Ra≥80
 Input voltage: AC100V-240V
 Driver: Built-in LED driver
 Operating temperature: -20°C~40°C



Beam Angle:




120°



WNZ00005



Material: PC
 Power: 24W
 CCT: 4000K/5000K/6000K
 Light source: EPISTAR SMD
 Light output: 2400lm
 Color rendering index: Ra≥80
 Input voltage: AC100V-240V
 Driver: Built-in LED driver
 Operating temperature: -20°C~40°C



Beam Angle:



120°






WNI00006-18W



Material: PC
 Power: 18W
 CCT: 3000K/4000K/6500K
 Light source: EPISTAR SMD
 Light output: 1440lm
 Color rendering index: Ra≥80
 Input voltage: AC220V-240V
 Driver: Built-in LED driver
 Operating temperature: -20°C~40°C




Beam Angle:



WNI00006-30W



Material: PC
 Power: 30W
 CCT: 3000K/4000K/6500K
 Light source: EPISTAR SMD
 Light output: 2400lm
 Color rendering index: Ra≥80
 Input voltage: AC220V-240V
 Driver: Built-in LED driver
 Operating temperature: -20°C~40°C



Beam Angle:

