

OUTDOOR PROWINDUCT


CANOPY LIGHT SERIES




WN-E001-1



Material: Aluminum+Toughened glass
 Voltage: AC220-240V
 Power: 20W
 Light source: CREE COB
 CCT: 3000K/4000K/5000K
 Safety Classification: Class I
 Driver: Built-in driver
 Control mode: Switch
 Working temps: -20°C~45°C




Beam Angle:




WN-E002-2



Material: Aluminum+Toughened glass
 Voltage: AC220-240V
 Power: 20W
 Light source: CREE COB
 CCT: 3000K/4000K/5000K
 Safety Classification: Class I
 Driver: Built-in driver
 Control mode: Switch
 Working temps: -20°C~45°C



Beam Angle:






WN-E318



Material: Aluminum+Toughened glass
 Voltage: AC220-240V
 Power: 12W
 Light source: CREE COB
 CCT: 3000K/4000K/5000K
 Safety Classification: Class I
 Driver: Built-in driver
 Control mode: Switch
 Working temps: -20°C-45°C



Beam Angle:




24°

WN-E328



Material: Aluminum+Toughened glass
 Voltage: AC220-240V
 Power: 25W
 Light source: CREE COB
 CCT: 3000K/4000K/5000K
 Safety Classification: Class I
 Driver: Built-in driver
 Control mode: Switch
 Working temps: -20°C-45°C



Beam Angle:



32°

